

15-AU50ES

QTY/CTN: 10

Economic Speed Dome Controller

Economic speed dome controller with keyboard and joystick, RS485 multi protocol, LCD display

FEATURES

- Easily ID, Protocols setup on OSD
- RS485 communication
- Set the address range of the dome camera and the decoder: 0~255



15-AU50E

QTY/CTN: 6

Speed Dome Controller

Speed dome controller with keyboard and joystick, RS485 multi protocols, LCD display.

FEATURES

- Multi-function keyboard
- Support RS485 and RS232 communication
- RJ45 connector and terminal block for RS485
- Set the address range of the dome camera: 0~255
- Speed level adjustable
- Designate part of image swapping function
- Directly control full functions of speed dome camera



15-AU50H

QTY/CTN: 6

3 Stage Joystick Speed Dome Controller

Speed dome controller with keyboard and joystick, RS485 multi protocols, LCD display.

FEATURES

- 3 stage joystick control
- Others identical to 15-AU50E



3 Stage Joystick

15-AU50H
3D Joystick
Twist to zoom
in and out



SPECIFICATION

Items	15-AU50ES	15-AU50E / 15-AU50H
Camera	Speed Dome Camera all Function OSD Camera all Function Zoom lens Camera all function	
Video Multiplexer	X	All Function
Baud Rate	2400, 4800, 9600 Bps	
Signal	RS-485 (Multi-Port Half-Duplex)	
Power	DC jack	
RS-485	RJ-45 Connector	Terminal block and RJ-45 connector
Input Voltage	12VDC (-15/+50%)	
Power Consumption	0.8W	3W
Safety Approval	CE, FCC	
Width	130 mm	330 mm
Height	190 mm	43 mm
Depth	64 mm	190 mm
Weight	525 g.	1106 g.
Operation Temperature	0°C~40°C	
Humidity	10%~90% RH, Non-condensation	
Storage Temperature	-10° ~ 60°C	
Transmitting Distance	1,200 M (Max)	