

## 15-DVR042M

## 15-DVR082M

## 15-DVR162M

QTY/CTN: 4


 H.264  
Compression


### 4 / 8 / 16CH H.264 Compression Digital Video Recorder

#### FEATURES

- H.264 video compression
- Recording quality/ rate adjustment per channel available.
- Support CMS (Central Management System)/3GPP
- Audio Backup / Audio Streaming
- Graphic User Interface ( GUI )
- Triplex, recording/ live-time & playback operation at the same time available
- Support time-point backup function under Ethernet remote control mode

Items	15-DVR042M	15-DVR082M	15-DVR162M
Video Input	4 x BNC	8 x BNC	16 x BNC
Video Looping	4 x BNC	8 x BNC	16 x BNC
Video Output	1xMain Monitor, 1xSpot Monitor, 1xS-video, 1X VGA		
Compression	H.264 Compression		
REC. Resolution	720x240 (NTSC), 720x288 (PAL) / 360 x 240 (NTSC), 360 x 288 (PAL)		
REC. Rate	60 fps (720x240), 50 fps (720x288) 120 fps (360x240), 100 fps (360x288)	120 fps (720x240), 100 fps (720x288) 240 fps (360x240), 200 fps (360x288)	
Recording Mode	Manual, Scheduled (5 Recording Schedule)		
Search Mode	Schedule, Event (Motion, Alarm)		
Storage	2 x SATA 3.5" HDD		
Backup	1 x USB 2.0 Slot For External USB Drive / HDD / CD-RW / DVD-RW		
Upgrade	Firmware Upgrade (USB FlashDrive)		
Connection	1 x RJ-45 Ethernet		
Protocols	Static IP, Dynamic IP, PPPoE		
IE Remote	Management, Monitoring, Recording, Playback		
3GPP	Yes		
Audio In/Out	1 x RCA In, 1 x RCA Out		
Alarm In/Out	4x In, 1 x Out	8x In, 1 x Out	16x In, 1 x Out
PTZ Protocols	1 x RS-485 (Pelco P, Pelco D & etc.)		
Motion Detect	Yes (30x24 grids)		
User Interface	Front Panel Buttons, IR Remote Controller, USB Optical Mouse		
Dimensions (W x H x D)	430x 88 x 382 mm		
Unit Weight	6.5 kg (without HDD)		
Operating Temperature	0 ~ 45 °C		
Operating Humidity	0 ~ 90%		
Power	DC12V		